

**IN THE CLAIMS**

Pursuant to 37 CFR §121(c), the claim listing, including the text of the claims, will serve to replace all prior versions of the claims, in the application.

Please cancel claims 23-26 and 30, without prejudice or disclaimer of their subject matter, amend claims 1, 28 and 29, and add claims 32-34 as follows:

1           1. (Currently Amended) A high-speed wireless data system for providing services for  
2 terminals of either a public wireless network or a private wireless network, the system  
3 comprising:

4           a first hub configured to relay data between a private base station in the private  
5 wireless network, a private base station controller in the private wireless network, a private  
6 packet data service node, ~~[[and]]~~ a private authentication system and a second hub, to receive  
7 a call connection request signal from a terminal through the private base station, to compare  
8 a server address included in an Unicast Access Terminal Identifier (UATI) assigned to the  
9 terminal with a set of server addresses pre-stored in the first hub, to transmit the call  
10 connection request signal to the private base station controller when a ~~sever~~ server address  
11 included in ~~[[a]]~~ the Unicast Access Terminal Identifier (UATI) assigned to the terminal ~~or~~  
12 ~~in a destination address in association with the call connection request signal is the same as~~  
13 ~~a sever address of~~ is among the set of server addresses pre-stored in the first hub, and to  
14 transmit the call connection request signal to a second hub when said sever address included  
15 in the Unicast Access Terminal Identifier (UATI) ~~or in the destination address is not the~~

16 ~~same as said sever address of~~ is not among the set of server addresses pre-stored in the first  
17 hub;

18 the second hub connected to a public base station, a public base station controller,  
19 ~~[[the]]~~ a data location register and a public network packet data service node while being  
20 connected to the first hub, the second hub receiving the call connection request signal of the  
21 terminal from the first hub and transmitting the call connection request signal to the public  
22 network base station controller; and

23 the data location register assigning the Unicast Access Terminal Identifier  
24 corresponding to the terminal, when the terminal enters a service area of the private base  
25 station.

Claims 2-26 (Cancelled)

1 27. (Previously Presented) The system according to claim 1, wherein:

2 the base station assigns an UATI to each of the terminals of the public wireless  
3 network and the private wireless network through a wireless channel to provide services of  
4 the high-speed wireless data system for each of the terminals;

5 the base station controller performs different authentications for the terminals  
6 according to the public wireless network and the private wireless network to one of which  
7 each of the terminals belongs, assignment of an UATI to each of the terminals, management  
8 of a session for each of the terminals, call connection and control of data transmitted to or

9 received by each of the terminals;

10 the private authentication system includes an authentication database for  
11 authenticating the terminal of the private wireless network;

12 the data location register having service information of the public wireless network  
13 terminal and information receives services from the private wireless network of the private  
14 wireless network terminal; and

15 the private packet data service node provides private wireless data services to the  
16 terminal of the private wireless network.

1 28. (Currently Amended) The system according to claim 27, wherein the base station  
2 and the base station controller assign an IP address for performing an IP telecommunication,  
3 and process data and signaling for the assigned IP address.

1 29. (Currently Amended) The system according to claim 27, wherein, upon the  
2 terminal of the private wireless network also being used in the public wireless network, the  
3 data location register stores terminal information of both the private wireless network and  
4 ~~the public wireless network in the terminal and assigns the UATI of the private wireless~~  
5 ~~network to the terminal when the terminal is located within a range of a predetermined base~~  
6 ~~station.~~

Claim 30. (Cancelled)

1           31. (Previously Presented) The system according to claim 27, wherein the private  
2 authentication system further includes a database for authentication of the terminal of the  
3 public wireless network.

1           32. (New) A method in a high-speed wireless data system, the method comprising the  
2 steps of:

3           storing a plurality of server addresses in a first hub, with the first hub being  
4 communicatively connected with at least one private base station in a private network, a  
5 private base station controller in the private wireless network controlling the at least one  
6 private base station, a private packet data service node, a private authentication system and  
7 a second hub, the second hub being communicatively connected with a public base station  
8 in a public network, a public base station controller, a data location register, and a public  
9 network packet data service node, and the private base station servicing a service area and  
10 the data location register assigning an Unicast Access Terminal Identifier (UATI) to each of  
11 a plurality of mobile terminals located within the service area, with the UATI containing a  
12 server address;

13           receiving an access request signal, from a mobile terminal at a private base station  
14 servicing a service area where the mobile terminal is located, with the access request signal  
15 comprising a destination address and an UATI of the mobile terminal;

16           transmitting the access request signal from the private base station to the first hub

17 according to the Internet protocol (IP) communication protocol;

18 making a determination, at the first hub, regarding whether the server address  
19 contained in the UATI received from the mobile terminal is among the plurality of server  
20 addresses stored in the first hub;

21 when the server address contained in the UATI received from the mobile terminal is  
22 among the plurality of server addresses stored in the first hub, transmitting the access request  
23 signal via the first hub to the private base station controller according to the Internet protocol  
24 (IP) communication protocol; and

25 when the server address contained in the UATI received from the mobile terminal is  
26 not among the plurality of server addresses stored in the first hub, transmitting the access  
27 request signal via the first hub to the second hub according to the Internet protocol (IP)  
28 communication protocol.

1 33. (New) The method of according to claim 31, the step of said making a  
2 determination further comprise, when the server address contained in a destination address  
3 in association with the call connection request signal is among the plurality of server  
4 addresses stored in the first hub, transmitting the access request signal via the first hub to the  
5 private base station controller according to the Internet protocol (IP) communication  
6 protocol.

1           34. (New) The system of according to claim 1, wherein the first hub configured to  
2           transmit the call connection request signal to the private base station controller when the  
3           server address included in a destination address in association with the call connection  
4           request signal is among a set of server addresses pre-stored in the first hub.